

## DB-FFAP

- Nitroterephthalic acid modified polyethylene glycol
- High polarity
- Temperature range from 40 °C to 250 °C
- Designed for the analysis of volatile fatty acids and phenols
- Replaces OV-351
- Bonded and cross-linked
- Solvent rinsable
- Close equivalent to USP Phase G35

**Note:** We do not recommend the use of water or methanol to rinse DB-FFAP GC columns.

**Similar Phases:** Stabilwax-DA, Nukol, 007-FFAP, BP21, AT-1000, OV-351

### DB-FFAP

| ID (mm) | Length (m) | Film (µm) | Temp Limits (°C) | 7 in Cage | 5 in Cage | 7890/6890 LTM II Module |
|---------|------------|-----------|------------------|-----------|-----------|-------------------------|
| 0.10    | 10         | 0.10      | 40 to 250        | 127-3212  |           | 127-3212LTM             |
|         | 15         | 0.10      | 40 to 250        | 127-32H2  |           | 127-32H2LTM             |
| 0.25    | 15         | 0.25      | 40 to 250        | 122-3212  |           |                         |
|         | 30         | 0.25      | 40 to 250        | 122-3232  | 122-3232E | 122-3232LTM             |
|         |            | 0.50      | 40 to 250        | 122-3233  |           |                         |
|         | 60         | 0.25      | 40 to 250        | 122-3262  | 122-3262E |                         |
|         |            | 0.50      | 40 to 250        | 122-3263  |           |                         |
| 0.32    | 15         | 0.25      | 40 to 250        | 123-3212  |           |                         |
|         | 25         | 0.50      | 40 to 250        | 123-3223  |           |                         |
|         | 30         | 0.25      | 40 to 250        | 123-3232  | 123-3232E | 123-3232LTM             |
|         |            | 0.50      | 40 to 250        | 123-3233  |           | 123-3233LTM             |
|         |            | 1.00      | 40 to 250        | 123-3234  |           | 123-3234LTM             |
|         | 50         | 0.50      | 40 to 250        | 123-3253  |           |                         |
|         | 60         | 0.25      | 40 to 250        | 123-3262  |           |                         |
|         |            | 0.50      | 40 to 250        | 123-3263  |           |                         |
|         | 1.00       | 40 to 250 | 123-3264         |           |           |                         |
| 0.45    | 30         | 0.85      | 40 to 250        | 124-3232  |           |                         |
| 0.53    | 10         | 1.00      | 40 to 250        | 125-32H2  |           |                         |
|         | 15         | 0.50      | 40 to 250        | 125-3217  |           | 125-3217LTM             |
|         |            | 1.00      | 40 to 250        | 125-3212  |           |                         |
|         | 30         | 0.25      | 40 to 250        | 125-3231  |           |                         |
|         |            | 0.50      | 40 to 250        | 125-3237  |           |                         |
|         |            | 1.00      | 40 to 250        | 125-3232  | 125-3232E |                         |
|         |            | 1.50      | 40 to 250        | 125-3233  |           |                         |
|         | 60         | 1.00      | 40 to 250        | 125-3262  |           |                         |