

DB-1

ID (mm)	Length (m)	Film (μm)	Temp Limits ($^{\circ}\text{C}$)	7 in Cage	5 in Cage	7890/6890	
						LTM II Module	
0.53	5	2.65	-60 to 325/350	125-100B			
		5.00	-60 to 325/350	125-1005		125-1005LTM	
7.5	1.50	-60 to 325/350	125-1002				
10	2.65	-60 to 260/280	125-10HB	125-10HBE	125-10HBLTM		
		5.00	-60 to 260/280	125-10H5			
15	0.15	-60 to 340/360	125-1011	125-1011E	125-1011LTM		
		0.25	-60 to 320/340	125-101K			
		0.50	-60 to 300/320	125-1017			
		1.00	-60 to 300/320	125-101J			
		1.50	-60 to 300/320	125-1012	125-1012E	125-1012LTM	
		3.00	-60 to 260/280	125-1014			
		5.00	-60 to 260/280	125-1015		125-1015LTM	
25	1.00	-60 to 300/320	125-102J				
		5.00	-60 to 260/280	125-1025		125-1025LTM	
30	0.10	-60 to 340/360	125-1039				
		0.25	-60 to 320/340	125-103K	125-103KE	125-103KLTM	
		0.50	-60 to 300/320	125-1037			
		1.00	-60 to 300/320	125-103J		125-103JLTM	
		1.50	-60 to 300/320	125-1032		125-1032LTM	
		2.65	-60 to 260/280	125-103B			
		3.00	-60 to 260/280	125-1034	125-1034E	125-1034LTM	
		5.00	-60 to 260/280	125-1035	125-1035E	125-1035LTM	
50	5.00	-60 to 260/280	125-1055				
60	1.00	-60 to 300/320	125-106J	125-106JE			
		-60 to 300/320	125-1062	125-1062E			
		-60 to 260/280	125-1064				
		-60 to 260/280	125-1065	125-1065E			
105	5.00	-60 to 260/280	125-10B5				