

DB-5ms

| ID (mm) | Length (m) | Film (µm) | Temp Limits (°C) | 7 in Cage | 5 in Cage | 7890/6890 |
|-------------|------------|----------------|-----------------------|-----------------|------------------|--------------------|
| | | | | | | LTM II Module |
| <i>0.18</i> | <i>20</i> | <i>0.18</i> | <i>-60 to 325/350</i> | <i>121-5522</i> | <i>121-5522E</i> | <i>121-5522LTM</i> |
| | | <i>0.36</i> | <i>-60 to 325/350</i> | <i>121-5523</i> | | <i>121-5523LTM</i> |
| | <i>40</i> | <i>0.18</i> | <i>-60 to 325/350</i> | <i>121-5542</i> | | |
| 0.20 | 12 | 0.33 | -60 to 325/350 | 128-5512 | | |
| | 25 | 0.33 | -60 to 325/350 | 128-5522 | | 128-5522LTM |
| | 50 | 0.33 | -60 to 325/350 | 128-5552 | | |
| 0.25 | 15 | 0.10 | -60 to 325/350 | 122-5511 | | 122-5511LTM |
| | | 0.25 | -60 to 325/350 | 122-5512 | | 122-5512LTM |
| | | 0.50 | -60 to 325/350 | 122-5516 | | |
| | | 1.00 | -60 to 325/350 | 122-5513 | | |
| | 25 | 0.25 | -60 to 325/350 | 122-5522 | | 122-5522LTM |
| | | 0.40 | -60 to 325/350 | | | |
| | 30 | 0.10 | -60 to 325/350 | 122-5531 | | |
| | | 0.25 | -60 to 325/350 | 122-5532 | 122-5532E | 122-5532LTM |
| | | 0.50 | -60 to 325/350 | 122-5536 | 122-5536E | |
| | | 1.00 | -60 to 325/350 | 122-5533 | 122-5533E | 122-5533LTM |
| | 50 | 0.25 | -60 to 325/350 | 122-5552 | | |
| | 60 | 0.10 | -60 to 325/350 | 122-5561 | | |
| 0.25 | | -60 to 325/350 | 122-5562 | 122-5562E | | |
| 1.00 | | -60 to 325/350 | 122-5563 | | | |
| 0.32 | 15 | 0.10 | -60 to 325/350 | 123-5511 | | |
| | | 0.25 | -60 to 325/350 | 123-5512 | | 123-5512LTM |
| | | 1.00 | -60 to 325/350 | 123-5513 | | 123-5513LTM |
| | 25 | 0.52 | -60 to 325/350 | 123-5526 | | |
| | 30 | 0.10 | -60 to 325/350 | 123-5531 | | |
| | | 0.25 | -60 to 325/350 | 123-5532 | 123-5532E | |
| | | 0.50 | -60 to 325/350 | 123-5536 | | 123-5536LTM |
| | | 1.00 | -60 to 325/350 | 123-5533 | | 123-5533LTM |
| | 60 | 0.10 | -60 to 325/350 | 123-5561 | | |
| | | 0.25 | -60 to 325/350 | 123-5562 | | |
| | | 0.50 | -60 to 325/350 | 123-5566 | | |
| | | 1.00 | -60 to 325/350 | 123-5563 | | |
| 0.53 | 15 | 1.50 | -60 to 300/320 | 125-5512 | | |
| | 30 | 0.50 | -60 to 300/320 | 125-5537 | | |
| | | 1.00 | -60 to 300/320 | 125-553J | | 125-553JLTM |
| | | 1.50 | -60 to 300/320 | 125-5532 | | 125-5532LTM |

Agilent J&W High Efficiency GC columns are displayed using italicized descriptions and part numbers