
## **VF-624ms and VF-1301ms**

- VF-624ms is designed for analyzing solvents according to EPA Methods 524, 624 and 8260, as well as USP 467
- VF-1301ms ultra-low-bleed thin-film has a similar selectivity to 624 and is suitable for semivolatile organic solvents, as well as PCBs and pesticides
- Enhanced selectivity for USP 467 eliminates co-elution of benzene and 1,2-dichloroethane
- Mid polarity
- Low bleed
- 0.15 mm id columns available for high efficiency GC and GC/MS analyses
- Supplied with an EZ-GRIP to simplify column installation, coupling and operation

**Similar Phases:** AT-624, Rxi-624 Sil MS, Rtx-624, PE-624, 007-624, 007-502, ZB-624



Structure of VF-624ms and VF-1301ms

## VF-624ms

ID (mm)	Length (m)	Film (µm)	Temp Limits (°C)	7 in Cage	5 in Cage
0.15	15	0.84	-40 to 280/300	CP9101	
	20	0.84	-40 to 280/300	CP9100	
	30	0.84	-40 to 280/300	CP9109	
	40	0.84	-40 to 280/300	CP9110	
0.25	30	1.40	-40 to 280/300	CP9102	CP9102I5
	60	1.40	-40 to 280/300	CP9103	CP9103I5
0.32	30	1.80	-40 to 280/300	CP9104	CP9104I5
	60	1.80	-40 to 280/300	CP9105	
0.53	30	3.00	-40 to 280/300	CP9106	CP9106I5
	60	3.00	-40 to 265/280	CP9107	
	75	3.00	-40 to 265/280	CP9108	

Agilent J&W High Efficiency GC columns are displayed using italicized descriptions and part numbers