


## Elite-WAX

The Elite-WAX column, a Polar Polyethylene glycol (PEG) stationary phase column, is a general purpose polar PEG phase commonly used for the analysis of polar compounds like alkenols, glycols and aldehydes. The extended operating temperature range up to 250 °C allowing analysis of compounds that have a wide volatility range. Selectivity of the Elite-WAX is comparable to other Carbowax® columns for compounds of intermediate to high polarity.

### Features and Benefits

- Temperature Range: 20 °C to 250 °C
- Equivalent to USP G14, G15, G16, G20 and G39 phases

Elite-WAX Structure



ID (mm)	df (µm)	Temp Limits (°C)	15 m Part No.	30 m Part No.	60 m Part No.
0.25	0.15	20 to 250	<b>N9316399</b>	<b>N9316402</b>	<b>N9316405</b>
	0.25	20 to 250	<b>N9316400</b>	<b>N9316403</b>	<b>N9316406</b>
	0.50	20 to 250	<b>N9316401</b>	<b>N9316404</b>	<b>N9316407</b>
0.32	0.15	20 to 250	<b>N9316408</b>	<b>N9316411</b>	
	0.25	20 to 250	<b>N9316409</b>	<b>N9316412</b>	<b>N9316416</b>
	0.50	20 to 250	<b>N9316410</b>	<b>N9316413</b>	<b>N9316417</b>
0.45	0.42	20 to 250	<b>N9316420</b>	<b>N9316422</b>	
	0.85	20 to 240/250	<b>N9316419</b>	<b>N9316421</b>	<b>N9316423</b>
	1.70	50 to 230	<b>N9316418</b>		
0.53	0.50	20 to 250	<b>N9316426</b>	<b>N9316428</b>	
	1.00	20 to 240/250	<b>N9316425</b>	<b>N9316427</b>	<b>N9316429</b>

### Elite-MWAX: Metal Column

ID (mm)	df (µm)	Temp Limits (°C)	30 m Part No.
0.53	1.00	20 to 240/250	<b>N9316478</b>